



CL-T100

COIN CHANGER



Money Controls



CL-T100

Description

Think fast and secure with Conlux CL-T100 coin changer. Specially created for the Asian vending market, it was designed with six key features (security, speed, convenience, intelligence, serviceability, and extendibility). This Conlux coin changer is focused on driving operator profitability.

The CLT100 coin changer can dispense up to 6 coins at once, enabling faster patron throughput. The intelligent algorithms automatically detect the best coin distribution, minimizing exact change situations. With the CL-T100 coin changer you can offer effective cash management and minimize your cost of ownership.



Benefits

Superior validation technology. Delivering the highest security for an excellent rejection rate

Keep your customers moving. Advanced coin sorting technology dispenses up to 6 coins at once—4x faster than the competition

Smart and interactive status checks. Operations panel diagnoses changer status in the field for operator convenience

Intelligent algorithm technology. Minimize exact change situations and maximize sales opportunities with as it studies machine patterns

Maintain and service from the field. Diagnostic LEDs on the changer minimize unnecessary asset replacements

Future-proof your investment. Flexible cassette and easy software updates for new coin adoption extends its lifetime and increases your ROI

COIN CHANGER



Specifications

Coin Diameter

- Coins 15mm - 28.50mm in diameter

Coin Thickness

- Coins 1.3mm - 3.0mm thick

Input speed

- 1.5 coins per second

Output Speed

- 6 coins per second

Interfaces Supported

- MDB, Executive

Operating Temperature

- -25°C to +60°C

Power Requirements

- 12 V DC - 24 V DC = Executive
- 34 V DC = MDB



COIN CHANGER

Tube/coin Level Recognition System

- Optical, Sonar



COIN CHANGER

Variants

Multi-Drop-Bus (MDB) / serial